

 **WARNING:** Before attempting to install or maintain this product, assure that your weapon is unloaded and the weapon safety is in the "safe" position

MOUNTING THE MAGNIFIER

- 1) Loosen the Lock Nut using the included wrench, and release the Quick Detach Lever. It should be a 90 degree angle.
- 2) Position the magnifier behind your red dot optic.
 - a. Mount as close as possible to your red dot, while still leaving room for operating your sight – about ¼"
- 3) Close the Quick Detach Lever and tighten the Quick Detach Tension Nut until optic doesn't move. **Do not over-tighten.**

OPERATION

To flip – Simply push the magnifier to the right side to disengage. Pull it back to give your red dot 3x magnification.

- **To focus** - If the red dot is blurry, use the Diopter Adjustment and adjust until dot appears clear.

CENTERING THE DOT

After zeroing your optic, use the Windage and Elevation Adjustment Caps to center the red dot within your magnifier's sight picture. *Note – this will not affect your point of impact for your red dot. It only centers the reticle in your magnifier.*

ADJUSTING FOR LOWER 1/3 COWITNESS

The DELTA is compatible with Absolute Cowitness red dot sights out of the box. If you need to change your setup for Lower 1/3 Cowitness red dots, follow these steps.

- 1) Flip the magnifier to the side, and remove the 2 screws on the bottom side of the optic mount
- 2) Remove the magnifier from the mount, and place the Cowitness Spacer on the mount where the magnifier originally was.
- 3) Reinstall the magnifier on top of the spacer, using the longer screws included for use with the Cowitness Spacer.
- 4) Hand tighten the screws to hold the magnifier in place, plus ¼ turn. **Do not over-tighten.**

WARRANTY

AT3 Tactical products carry a lifetime warranty. Full details are available at at3tactical.com/warranty
If you have any issues or need a replacement, please contact us via email: support@at3tactical.com

